
DR30SF-WH/BK/SN

3.5 inch LED Square Ultra Slim Recessed downlight(Air tight)



Job Information				
Project Name		Туре		
Location				
Quantity		Date		
Contact/ Name				
Notes				

Body

- Durable airtight aluminum
- White polycarbonate diffuser lens for low glare

LED Characteristics

- 7-Watt LED Module
- · Minimal heat emission
- Up to 500 Lumens
- Superior LED Performance and lifespan
- Excellent Color rendering with Spotlight

Dimming

- 10%-100% dimming capability
- Compatible with industry TRIAC/ELV dimmers (contact factory for compatible dimmers list)

Environment

- · Suitable for wet locations
- · Suitable for insulated ceiling application
- Can be installed indoor and for outdoor applications

Mounting

- Included two springs loaded cilps to attach to any ceilling material
- The slim profile allow to be mounted under joists or dock work
- Easier intallation with 3 5/8" round back

Description

 DR30SF, a 7watt 3.5-inch All CCT slim profile square flat LED panel is a high-performance, easy to install downlight. It offers excellent light output, energy efficiency, and streamlined design. Suitable for wet location and use in soffits.

Beam Spread

• 110 degree beam spread

LED Driver

- Extruded aluminum junction box with integrated 210mA dimmable driver included
- Class II electronic LED driver with 100-125V AC input;
- includeds an 12" cable from driver to fixture

Quick Connect Push-in Terminals

• Three "Quick Connect" Push-in terminals for fast and easy wiring

Operating Temperature

• -20°C - 40°C (-4°F - 104°F)



















SPECIFICATION			
Application	Ceiling Recessed Mount	Energy Star	YES
Approved Location	Wet	Input	100-125V AC, 60Hz, 0.09A
Beam Angle	110	LM 79	YES
CCT	2700K/3000K/3500K/4000K/5000K	LM 80	YES
Certification	cETLus	Lumens	Up to 500
Class II	YES	Lumens per Watt	72.5
Color	White/Black/Brushed Nickel	Power Factor	>0.95
CRI	95+	Projected Life	5 Years
Dimming	YES	Wattage	7 Watt
Dimming Tech	TRIAC/ELV	Cut-Size	3 5/8"

