
DR60RG-WH

6 inch LED Gimbal Slim Recessed downlight



Job Informa	
Project Name	Type
Location	
Quantity	Date
Contact/ Name	
Notes	

- Body

 Durable airtight aluminum
- White polycarbonate diffuser lens for low glare

LED Characteristics

- •15-Watt LED Module
- · Minimal heat emission

- Up to 1580 Lumens
 Superior LED Performance and lifespan
 Excellent Color rendering with Spotlight

Dimming

- 10%-100% dimming capability
- · Compatible with industry TRIAC/ELV dimmers (contact factory for compatible dimmers list)

Environment

- Suitable for wet locations
- · Suitable for insulated ceiling application
- · Can be installed indoor and for outdoor applications

- · Included two springs loaded cilps to attach to any ceilling material
- The slim profile allow to be mounted dock work

Description

• DR60RG, a 15watt 6-inch All CCT slim profile round flat LED panel is a high-performance, easy to install downlight. It offers excellent light output, energy efficiency, and streamlined design. Suitable for wet location and use

Beam Spread

· 38 degree beam spread

LED Driver

- Extruded aluminum junction box with integrated 210mA dimmable driver included
- Class II electronic LED driver with 100-125V AC input;
 includeds an 12" cable from driver to fixture

Quick Connect Push-in Terminals
• Three "Quick Connect" Push-in terminals for fast and easy wiring

Operating Temperature • -20°C - 40°C (-4°F - 104°F)



















SPECIFICATION			
Application	Ceiling Recessed Mount	Energy Star	YES
Approved Location	Wet	Input	100-125V AC, 60Hz, 0.09A
Beam Angle	38	LM 79	YES
ССТ	2700K/3000K/3500K/4000K/5000K	LM 80	YES
Certification	cETLus	Lumens	Up to 1580
Class II	YES	Lumens per Watt	105.3
Color	White	Power Factor	>0.95
CRI	90+	Projected Life	5 Years
Dimming	YES	Wattage	15 Watt
Dimming Tech	TRIAC/ELV	Cut-Size	6 5/16"

