
# DR30RG-WH/BK/SN

# 3.5 inch LED Round Gimbal Ultra Slim Recessed downlight(Air tight)



ation	
	Туре
	Date
	ation

#### Body

- Durable airtight aluminum
- · White polycarbonate diffuser lens for low glare

# **LED Characteristics**

- 9-Watt LED Module
- Minimal heat emission
- Up to 800 Lumens
- Superior LED Performance and lifespan
- Excellent Color rendering with Spotlight

# Dimming

- 10%-100% dimming capability
   Compatible with industry TRIAC/ELV dimmers (contact factory for compatible dimmers list)

#### Environment

- Suitable for wet locations
- · Suitable for insulated ceiling application
- Can be installed indoor and for outdoor applications

#### Mounting

SPECIFICATION

- · Included two springs loaded cilps to attach to any ceilling material
- The slim profile allow to be mounted dock work

#### Description

• DR30RG, a 9watt 3.5 inch All CCT slim profile round flat LED panel is a high-performance, easy to install downlight. It offers excellent light output, energy efficiency, and streamlined design. Suitable for wet location and use

### **Beam Spread**

· 38 degree beam spread

#### LED Driver

- Extruded junction box with integrated 210mA dimmable driver included
- Class II electronic LED driver with 100-125V AC input;
  includeds an 12" cable from driver to fixture

#### **Quick Connect Push-in Terminals**

• Three "Quick Connect" Push-in terminals for fast and easy

# **Operating Temperature**

--20°C - 40°C (-4°F - 104°F)




















Application	Ceiling Recessed Mount
Approved Location	Wet
Beam Angle	38
CCT	2700K/3000K/3500K/4000K/5000K
Certification	cETLus
Class II	YES
Color	White/Black/Brushed Nickel
CRI	90+

Dimming

Dimming Tech

Energy Star	YES
Input	100-125V AC, 60Hz, 0.09A
LM 79	YES
LM 80	YES
Lumens	Up to 800
Lumens per Watt	88.90
Power Factor	>0.95
Projected Life	5 Years
Wattage	9 Watt
Cut-Size	3 3/4"

ССТ	LUMENS
2700K	750LM
3000K	750LM
3500K	800LM
4000K	800LM
5000K	750LM



YES

TRIAC/ELV

