

# 30TL-L

## 3" 5CCT LED TRIMLESS POT LIGHT

### Job Information

|                     |  |             |
|---------------------|--|-------------|
| <b>Project Name</b> |  | <b>Type</b> |
| <b>Location</b>     |  |             |
| <b>Quantity</b>     |  | <b>Date</b> |
| <b>Contact/Name</b> |  |             |
| <b>Notes</b>        |  |             |

#### Body

- Durable Aluminium body
- White polycarbonate diffuser lens for low glare

#### LED Characteristics

- 12-Watt LED Module
- Minimal heat emission
- Up to 1100 Lumens
- Superior LED Performance and lifespan
- Excellent Color rendering with Spotlight

#### Dimming

- 10%-100% dimming capability
- Compatible with TRIAC/ELV dimmers

#### Environment

- Suitable for wet locations
- Suitable for insulated ceiling application
- Can be installed indoor and for outdoor applications

#### Mounting

- Webbed plate for mudding
- Four flat head screws

#### Description

• 30TL-L, a 12watt 3-inch 5CCT led trimless pot light is a high-performance, easy to install downlight. It offers excellent light output, energy efficiency, and streamline design. Suitable for wet location and use under soffits.

#### Beam Spread

- 38 degree beam spread

#### LED Driver

- Extruded iron junction box with integrated 210mA dimmable driver included
- LVLE output LED driver with 100-125V AC input; included 12inch cable from the driver to fixture.


#### Quick Connect Push-in Terminals

- Three "Quick Connect" Push-in terminals for fast and easy wiring

#### Operating Temperature

- -20°C - 40°C (-4°F - 104°F)

#### Optional



Honey comb louver (included in box)

- Anti glare (it may diminish lumen output by 10-25%)



### SPECIFICATION

|                          |                                      |                        |                                 |
|--------------------------|--------------------------------------|------------------------|---------------------------------|
| <b>Application</b>       | <b>Ceiling Recessed Mount</b>        | <b>Energy Star</b>     | <b>YES</b>                      |
| <b>Approved Location</b> | <b>Wet</b>                           | <b>Input</b>           | <b>100-125V AC, 60Hz, 0.09A</b> |
| <b>Beam Angle</b>        | <b>38</b>                            | <b>LM 79</b>           | <b>YES</b>                      |
| <b>CCT</b>               | <b>2700K/3000K/3500K/4000K/5000K</b> | <b>LM 80</b>           | <b>YES</b>                      |
| <b>Certification</b>     | <b>cETLus</b>                        | <b>Lumens</b>          | <b>Up to 1100</b>               |
| <b>Class II</b>          | <b>YES</b>                           | <b>Lumens per Watt</b> | <b>91.67</b>                    |
| <b>Color</b>             | <b>White</b>                         | <b>Power Factor</b>    | <b>&gt;0.90</b>                 |
| <b>CRI</b>               | <b>90+</b>                           | <b>Projected Life</b>  | <b>5 Years</b>                  |
| <b>Dimming</b>           | <b>YES</b>                           | <b>Wattage</b>         | <b>12 Watt</b>                  |
| <b>Dimming Tech</b>      | <b>TRIAC/ELV</b>                     | <b>Cut-Size</b>        | <b>3 3/8"</b>                   |

