

DR35RB-WH/BK/SN

3.5 inch 5CCT LED Baffle Recessed downlight(Air tight)

DR	SIZE	SHAPE	FEATURE	COLOR
20 : 2"	20 35 40	RB : Round		WH BK SN
35 : 3.5"	40	RB : Round	D Dim to Warm	WH BK SN
40 : 4"	35	SB : Square	- Turned F Fixed	WH BK SN
WH : White BK : Black SN : Silver	25	RB : Round	H Night Halo	WH BK SN

Job Information		
Project Name		Type
Location		
Quantity		Date
Contact/ Name		
Notes		

Body

- Durable airtight aluminum
- White polycarbonate diffuser lens for low glare

LED Characteristics

- 12-Watt LED Module
- Minimal heat emission
- Up to 1100 Lumens
- Superior LED Performance and lifespan
- Excellent Color rendering with Spotlight

Dimming

- 10%-100% dimming capability
- Compatible with industry TRIAC/ELV dimmers (contact factory for compatible dimmers list)

Environment

- Suitable for wet locations
- Suitable for insulated ceiling application
- Can be installed indoor and for outdoor applications

Mounting

- Included two springs loaded clips to attach to any ceiling material
- The slim profile allow to be mounted dock work

Description

- DR35RB, a 12 watt 3.5 inch All CCT round baffle LED panel is a high-performance, easy to install downlight. It offers excellent light output, energy efficiency, and streamlined design. Suitable for wet location and use in soffits.

Beam Spread

- 38 degree beam spread

LED Driver

- Extruded junction box with integrated 210mA dimmable driver included
- Class II electronic LED driver with 100-125V AC input; includes an 12" cable from driver to fixture

Quick Connect Push-in Terminals

- Three "Quick Connect" Push-in terminals for fast and easy wiring

Operating Temperature

- -20°C - 40°C (-4°F - 104°F)



SPECIFICATION				CCT	LUMENS
Application	Ceiling Recessed Mount	Energy Star	YES	2700K	1000LM
Approved Location	Wet	Input	100-125V AC, 60Hz, 0.09A	3000K	1030LM
Beam Angle	38	LM 79	YES	3500K	1060LM
CCT	2700K/3000K/3500K/4000K/5000K	LM 80	YES	4000K	1100LM
Certification	cETLus	Lumens	Up to 1100	5000K	1060LM
Class II	YES	Lumens per Watt	94.4		
Color	White/Black/Brushed Nickel	Power Factor	>0.95		
CRI	90+	Projected Life	5 Years		
Dimming	YES	Wattage	12 Watt		
Dimming Tech	TRIAC/ELV	Cut-Size	3 1/2"		

