

30TL-L-D

3" Dim to Warm LED Trimless Pot Light

Job Information

Project Name		Type
Location		
Quantity		Date
Contact/Name		
Notes		

Body

- Durable Aluminium body
- White polycarbonate diffuser lens for low glare

LED Characteristics

- 12-Watt LED Module
- Minimal heat emission
- Up to 970 Lumens
- Superior LED Performance and lifespan
- Excellent Color rendering with Spotlight

Dimming

- 10%-100% dimming capability
- Compatible with TRIAC/ELV dimmers

Environment

- Suitable for wet locations
- Suitable for insulated ceiling application
- Can be installed indoor and for outdoor applications

Mounting

- Webbed plate for mudding
- Four flat head screws

Description

- 30TL-L-D, a 12watt 3-inch dim-to-warm led trimless pot light is a high-performance, easy to install downlight. It offers excellent light output, energy efficiency, and streamline design. Suitable for wet location and use under soffits.

Beam Spread

- 38 degree beam spread

LED Driver

- Extruded iron junction box with integrated 210mA dimmable driver included
- LVLE output LED driver with 100-125V AC input; included 12inch cable from the driver to fixture.


Quick Connect Push-in Terminals

- Three "Quick Connect" Push-in terminals for fast and easy wiring

Operating Temperature

- -20°C - 40°C (-4°F - 104°F)

Optional



Honey comb louver (included in box)

- Anti glare (it may diminish lumen output by 10-25%)



SPECIFICATION

Application	Ceiling Recessed Mount	Energy Star	YES
Approved Location	Wet	Input	100-125V AC, 60Hz, 0.09A
Beam Angle	38	LM 79	YES
CCT	2200K-3000K	LM 80	YES
Certification	cETLus	Lumens	Up to 970
Class II	YES	Lumens per Watt	80.83
Color	White	Power Factor	>0.90
CRI	90+	Projected Life	5 Years
Dimming	YES	Wattage	12 Watt
Dimming Tech	TRIAC/ELV	Cut-Size	3 3/8"

